

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-130909

(43)Date of publication of application : 18.05.1999

(51)Int.Cl.

C08L 9/00  
B60C 1/00  
// (C08L 9/00  
C08L 23:00 )  
(C08L 9/00  
C08L 93:00 )

(21)Application number : 09-315837

(71)Applicant : TOYO TIRE &amp; RUBBER CO LTD

(22)Date of filing : 30.10.1997

(72)Inventor : IWAMA SATOSHI  
MAEDA KIETSU

## (54) RUBBER COMPOSITION FOR TIRE TRED

## (57)Abstract:

PROBLEM TO BE SOLVED: To obtain a compsn. having excellent wet-friction property, wear resistance, and rubber hardness and besides having little toxic components, by blending it with a processing oil comprising a non-aromatic oil and a resin component comprising one of an aromatic hydrocarbon, a petroleum resin, etc.

SOLUTION: A processing oil comprising a non-aromatic oil, e.g. a paraffinic oil or a naphthenic oil, pref. having a polycyclic, aromatic compd. content of less than 3 wt.%, is blended with a resin component comprising a resin of an aliphatic hydrocarbon resin, a petroleum resin, a rosin derivative, a cumarone resin, and a phenol terpene resin, pref. an aliphatic hydrocarbon resin, a rosin derivative or a petroleum resin. The non-aromatic oil has pref. a dynamic viscosity at 100° C of 16 cSt or less, and a carbon type ratio, in the aromatic ring part, of 15% or less. A raw material rubber of 100 pts.wt. is blended pref. with the processing oil of 5-70 pts.wt. and the resin component of 5-50 pts.wt.

## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office